

MARTIN FINGER SHIELD™ GARAGE DOOR SYSTEM



INSTRUCTION MANUAL (STEEL/COPPER AND WOOD DOORS)



A8949

ISO 9001



MARTIN DOOR MFG.

WARNING



ATTENTION

THIS IS THE WORLD'S FINEST, SAFEST DOOR. HOWEVER, UNTRAINED OR NEGLECTFUL INSTALLING, ADJUSTING, AND SERVICING CAN BE DANGEROUS. THE SPRINGS AND RELATED PARTS CAN CAUSE SERIOUS INJURY OR DEATH!

MAINTENANCE

- Oil all hinges, roller shafts, and spring coils, using a high quality 10/40 motor oil. Oil yearly for a smooth operation. Do not allow parts to squeak!
- Wax yearly the leading edge of metal door Finger Shields or inside wood door section joints. Also wax Reverse Angle Shields or jambs (where door seals while closing).
- As needed, use lightly oiled cloth to wipe galvanized parts to help retain clean galvanized look. In damp, wet areas, galvanized parts may require painting to help prevent rust.
- Touch-up paint not recommended on steel doors. Read "Painting Theory" on back page.
- As needed, wash away dirt, salt residue, etc. from steel door sections. Automobile type cleaners and waxes may improve the look and prolong the life of aged paint or a neglected steel door. Frequent waxing or painting may be required in extremely damp, salty or caustic areas. For wood doors see "WOOD DOOR NOTES" page.
- Clean the acrylic windows with a soft wet cloth. Remove scratches in the acrylic window pane with a quality plastic window cleaner.

DOOR OPENERS (We recommend Martin Door Openers)

- Always keep the garage door in full view while using the electric opener.
- Monthly check the automatic reverse function, following the manufacturer's electric opener instructions.
- Martin Doors are designed to reduce risk of entrapment and injury to children and adults. Roller Shields, Finger Shields, Low Profile Hinges, Reverse Angle Shields, Inside Lift Cables, Rolled Steel Edges, etc., are all designed for added child safety.
- Remove all pull down ropes and disable any garage door locking mechanism.
- The top door section should have a full length strut for center mounted openers. Side mounted openers may not require a strut on single size doors under 12'3" (3734) wide.

NOXIOUS FUMES

DO NOT completely weather seal this door! Vent according to local building codes. CAUTION! Low levels of carbon monoxide in the garage and home can cause headaches and flu-like symptoms. Additional venting may be required to help reduce the health risks associated with combustible fuels and noxious fumes.

INSULATION

The insulation used in Martin Doors comply with all known building codes. It has been tested and approved by Omega Point Laboratories and meets the UBC-26-8 standard for smoke and flame spread. The insulation is removable and reusable which helps the environment by reducing landfill waste!

DENT REPAIR (Steel Doors)

Martin regular and insulated door sections are rated among the most dent resistant in the world. They do not require insulation bonded to them for strength. Because of this unique construction it may not be necessary to replace a door section or a complete door to avoid the prolonged appearance of a damaged surface. For dent repair see page 18.

WARRANTY

The Martin Warranty is to the original owner. Lifetime Ltd. for most residential doors (12 year Ltd. on Montana). Six Year Ltd. for commercial, rentals, and 5 yr. on wood doors. Replacement part shipping and labor costs are not included. Springs have life cycle limits. Note: with proper care and maintenance all Martin Doors (except springs) are designed to last a lifetime. Contact your Martin Dealer for details on the full written warranty and limitations.

MARTIN FINGER SHIELD™ GARAGE DOOR SYSTEM*

•SAFETY SECTION ASSEMBLY •SAFETY TRACK ASSEMBLY •SAFETY SPRING ASSEMBLY
 *HELPS PREVENT GARAGE DOOR INJURIES TO CHILDREN AND ADULTS

